

Technical Data

Ancillary Products

Ref: TI 006

Coretek 1 Adhesive

A high quality sodium silicate based cold to cold adhesive. Ideal for general repair & joint sealing in most cold setting systems. Available in several pack sizes it makes an ideal multi use adhesive for most foundries.

Coretek Putty

The main use for this multi-purpose putty is, as a core and mould joint filler. It can also be used for general repairs and imperfections on the mould or core surface. Coretek Putty is easily applied by either hand or trowel giving a smooth, quick drying finish.

Striptek 5

Still the most popular type of release agent this air-drying talc based product is suitable for application to most types of core & mould pattern equipment. It's excellent release make it ideal for medium to large moulding where older pattern equipment is in use. It is also useful for coating mixing chambers as an aid to cleaning.

Striptek 35

This conventional water based silicone emulsion is ideal for use on all hot curing processes, Hot-box, Warm-box & Shell systems. It is formulated especially for spray application but can be brushed or flooded.

Trigel

A specially formulated aluminium based release agent which is becoming increasingly popular in all types of foundry. It is offered in two grades: -

LD - Is a low viscosity paint ideal for large or small patterns giving good definition and no loss of detail. For use on all no-bake systems.

HD - This is a paste like paint which can be brushed on larger tooling or heavy duty jobs. Its main use is on continuous mixer blades and chambers reducing end of shift cleaning time.

Ancillary Products

Ref: TI 006

Striptek Metal Cleaner

A special non-flammable solvent for cleaning most urethane cold-box tooling and equipment. It eases release and combats resin wipe or build up on core boxes, blowing heads, & sand chutes etc.

Isopropanol

This solvent is offered either as a recovered foundry grade solvent for most applications or as virgin product for the most demanding uses. Both grades are less than 1% water and can be used for thinning most foundry coatings.

Packaging

Pack /Size	1 ltr	5 ltr	25 ltr	50 ltr	200 ltr
Coretek 1	x	x	x		
Coretek Putty		x			
Striptek 5		x	x	x	
Striptek 35			x	x	x
Trigel (LD)		x	x		
Trigel (HD)		x	x		
Metal Cleaner		x	x	x	
Isopropanol				x	x

(x = available)

For more information on individual products and their application contact our technical sales staff.

HEALTH & SAFETY

Health and safety sheets on individual product are available separately on request.

March 2003